



**kadriumdesign**™/MC

# TAMBOUR DOORS Milano Box



**Max. height:** 1500mm (59")  
**Min. height:** 508mm (20")\*  
\* this is the minimum height for a 12" opening.

**Max. width:** 900mm (35 7/16")  
**Min. width:** 381mm (15")  
**Min. depth:** 300mm (11 13/16")\*  
\* Minimum cabinet depth necessary to install the tambour door system.

For cabinets with a 5/8" thickness

**Finishes:**  
Anodized Aluminum  
Stainless Steel



### Interior Profiles

**2125 SN**  
Anodized aluminum finish.

**2125 SN-W**  
Anodized aluminum finish - Wind.

**2125 A2 SS**  
Stainless steel finish.

**2125 A2-W SS**  
Stainless steel finish - Wind.



### Frame

The frame is the core of the opening system. It is made of the coiling guides, the counter balance shaft and the frame tube profile.



### Counter Balance Shaft

Tambour doors opens smoothly and stays in position, even when partly open, thanks to the Counter Balance Shaft. Available in two types, for doors up to 600mm or up to 900mm wide.

300

### Coiling Guide

The coiling guide insures that the tambour door safely rolls into place when opened.

134



Frame

Side Profile


Top Profile

Interior Profiles


Handle Profile

Base Profile

When ordering Tambour doors, it must be specified if the cabinet is with or without a base. (a box on a countertop, as the picture on the upper left, has no base.)



Base



No Base